







Technical Dimensions (mm)




Image



Terminal Dimensions (mm)

Standard
 Terminal: F11



Technical Specification

Output	Nominal Voltage	12.8V
	Nominal Capacity	100Ah
	Energy	1280Wh
Terminal Type	Standard Terminal	F11
Container Material	Standard Option	ABS
	Flame Retardant Option (FR)	ABS (UL94:VO)
	IP Class	IP65
Standard Charge	Charge Voltage	14.6±0.2V
	Charge Mode	0.2C (CC) charge to 14.6V, then charge (0.02C) (CV)
	Charge Current	20A
	Max. Charge Current	100A
	Standard Charge Current	14.6V ± 0.2V
Standard Discharge	Continuous Current	100A
	Max. Pulse Current	200A(<3s)
	Discharge Cut-off Voltage	10V
Internal Resistance	≤20mΩ	
Discharge Characteristics	Operating Temp Range	Charge: 0 ~ 55°C
		Discharge: -20 ~ 60°C
		Storage: -20 ~ 45°C
Efficiency of Charge	100% @0.5C	
Efficiency of Discharge	96~99% @1C	
Cycle Life	≥2000 cycles @ 1C 100%DOD	
Battery Management System	Complete with BMS unit measuring current, voltage, single cell surface temperature and the ambient temperature of the battery.	


Self Discharge

Ultracell® LIT batteries may be stored for up to 2 years at 25°C and then a refresh charge is required. For higher temperatures the time intervals will be shorter.


Transportation

Ultracell® LIT Batteries will be at 30% State of Charge when shipped in accordance to the applicable international and national government regulations. To prevent damage during transit, ensure packaging is safe and secure. Keep battery dry and away from direct sunlight. Suitable for all transportation vehicles.


Different Rate Discharge Curve (25°C)




Different Temperature Discharge Curve (0.5C)




State of Charge Curve (0.5C, 25°C)



Charging Characteristics (0.5C, 25°C)



Cycle Life on D.O.D (25°C)



Temperature on Self Discharge Curve

